

Kodak CFH-V10 Specifications:

Camera	
Image Sensor	2M 1/3.2 inch CMOS sensor
Lens	Focal length: 3.8mm, F2.2
View Angle	Horizontal: 71° Vertical: 39° Diagnol: 85°
IR Leds	4 medium power IR leds, 850nm IR-CUT imbedded for dual films switching 8 meter illumination distance
IR Mode	Always on Always off Auto mode ● IR turns on when illuminance is around to 3±2 lux ● IR turns off when illuminance is around to 6±3 lux
Ambient Light Sensor	RoHS compliant 560nm illuminance detector
Video	
Codecs	H.264
Resolution	320x180, 640x360, 1280x720
Frame Rate	Up to 30 frames
Video Features	Adjust resolution, frame rate and quality Flip and mirror image for upside down installation
Audio	
Audio in	Built-in Microphone, -38dB±2dB
Audio out	Yes
Audio compression	G.711, PCM, AAC
Networking	
Network Interface <input type="checkbox"/>	802.11b/g/n WLAN with 2x2 MIMO
Wireless Connectivity <input type="checkbox"/>	802.11b/g/n Wireless with WEP/WPA/WPA2 security
Radio Specifications	RF band: ISM Band 2.4GHz Channels: Varies by country RF Power Output ● 802.11n: 15±2 dBm Average ● 802.11g: 15±2 dBm Average ● 802.11b: 18±2 dBm Average
Antenna	Type: Chip antenna, SMD Gain: 1.5dBm peak Efficiency: about 70%
General	
System	Processor: MT7620A Speed: 580MHz DRAM: 128MB Flash: 16MB

Button	<p>RESET Button</p> <ul style="list-style-type: none"> ● Reset system: Press less than 1 seconds to reset the system ● Factory default: Press and hold 15 seconds to restore the factory default settings
Switch	Setup mode switch: Turn setup mode on and off.
LEDs	<p>Setup Mode LED</p> <ul style="list-style-type: none"> ● Solid Green: Setup mode on ● Orange: In progress to switch to Setup Mode ● No light: Setup mode off <p>Network LED</p> <ul style="list-style-type: none"> ● Solid Orange: Local network ok ● Solid Green: Connection to seedonk server ok ● Flashing Orange: No local network yet ● Flashing Green: Global internet ok <p>System LED</p> <ul style="list-style-type: none"> ● Solid green: system on.
Connectors	DC Jacket
Power	External AC-to-DC switching power adapter input: 100-240V AC, 50/60Hz, Output: 5V DC, 1.0A
Max Power Consumption	<4W
Operation Conditions	<p>Temperature: 32°F to 104°F (0°C to 40°C)</p> <p>Humidity: 20-80% RH Non-Condensing</p>
Storage Conditions	<p>Temperature: 14°F to 140°F (-20°C to 60°C)</p> <p>Humidity: 5%-95% RH Non-Condensing</p>
Dimensions (W x D x H)	<p>Including the bracket and stand: 2.7" x 3.7" x 4.9" (67.7mm x 95mm x 123.3mm)</p> <p>Camera only: 2.5" x 1.4" x 4.1"(64.1mm x 36.2mm x 104.1mm)</p>
Unit Weight	<p>Including the bracket and stand: 140g</p> <p>Package: 380g</p>
Package Contents	<p>Wireless N Day/Night Network Camera</p> <p>Power Adapter</p> <p>Camera Base and Mounting Kit</p> <p>Quick Installation Guide</p>
Certifications	<p>FCC Class B</p> <p>CE</p> <p>RoHS</p>

<http://showroomshops.de/kodak.html>

